



THE TIGER.

SILO | EPS FISH BOXES

Compaction system for pre-shredded EPS fish boxes.

Model variant for direct connection to a silo.

Corrosion-protected design for processing wet EPS.

Used for daily medium to very large processing quantities.

Suitable for part sizes up to 80 mm.

TIGER 200 SILO | EPS FISH BOXES

Throughput ¹⁾	up to 50 Kg/h
Recommended performance range ¹⁾	80 - 250 Kg/day
Achievable compaction density ¹⁾	up to 250-350 kg/m ³
Processable material densities	up to 40 g/l
Processable part size	up to 80 mm
Inlet size for Silo connection	Dia 600 mm
Block size	210 x 210 mm
Installation dimensions (L x W x H) ²⁾	4.840 x 1.270 x 1.055 mm
Machine weight ²⁾	approx. 675 kg
Electrical connected load ²⁾	4,25 kW (16 Amp)
Supply voltage (EU)	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz
Marking	CE

Materials

EPS fish boxes pre-shredded, wet

Industries

Fish industry

Fish markets

Delicatessens

Options

Automatic block separating system

Block lifting crane with gripper

Individually customized silo size

Symbol image



¹⁾ Depending on material type and material density ²⁾ Basic machine without silo and options

TIGER 250 SILO | EPS FISH BOXES

Throughput ¹⁾	up to 80 Kg/h
Recommended performance range ¹⁾	150 - 400 Kg/day
Achievable compaction density ¹⁾	up to 250-350 kg/m ³
Processable material densities	up to 40 g/l
Processable part size	up to 80 mm
Inlet size for Silo connection	Dia 600 mm
Block size	260 x 260 mm
Installation dimensions (L x W x H) ²⁾	4.990 x 1.270 x 1.055 mm
Machine weight ²⁾	approx. 800 kg
Electrical connected load ²⁾	5,75 kW (16 Amp)
Supply voltage (EU)	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz
Marking	CE

Materials

EPS fish boxes pre-shredded, wet

Industries

Fish industry

Fish markets

Delicatessens

Options

Automatic block separating system

Block lifting crane with gripper

Individually customized silo size

Symbol image



TIGER 300 SILO | EPS FISH BOXES

Throughput ¹⁾	up to 120 Kg/h
Recommended performance range ¹⁾	200 - 700 Kg/day
Achievable compaction density ¹⁾	up to 250-350 kg/m ³
Processable material densities	up to 40 g/l
Processable part size	up to 80 mm
Inlet size for Silo connection	Dia 700 mm
Block size	320 x 320 mm
Installation dimensions (L x W x H) ²⁾	5.350 x 1.370 x 1.175 mm
Machine weight ²⁾	approx. 1.250 kg
Electrical connected load ²⁾	7,87 kW (32 Amp)
Supply voltage (EU)	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz
Marking	CE

Materials

EPS fish boxes pre-shredded, wet

Industries

Fish industry

Fish markets

Delicatessens

Options

Automatic block separating system

Block lifting crane with gripper

Individually customized silo size

Symbol image



¹⁾ Depending on material type and material density ²⁾ Basic machine without silo and options

TIGER 400 SILO | EPS FISH BOXES

Throughput ¹⁾	up to 200 Kg/h
Recommended performance range ¹⁾	400 - 1.500 Kg/day
Achievable compaction density ¹⁾	up to 250-350 kg/m ³
Processable material densities	up to 40 g/l
Processable part size	up to 80 mm
Inlet size for Silo connection	Dia 700 mm
Block size	400 x 400 mm
Installation dimensions (L x W x H) ²⁾	5.780 x 1.370 x 1.175 mm
Machine weight ²⁾	approx. 1.550 kg
Electrical connected load ²⁾	15,37 kW (64 Amp)
Supply voltage (EU)	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz
Marking	CE

Materials

EPS fish boxes pre-shredded, wet

Industries

Fish industry

Fish markets

Delicatessens

Options

Automatic block separating system

Block lifting crane with gripper

Individually customized silo size

Symbol image



TIGER 500 SILO | EPS FISH BOXES

Throughput ¹⁾	up to 400 - 500 Kg/h
Recommended performance range ¹⁾	1.000 - 3.000 Kg/day
Achievable compaction density ¹⁾	up to 250-350 kg/m ³
Processable material densities	up to 40 g/l
Processable part size	up to 80 mm
Inlet size for Silo connection	Dia 700 mm
Block size	500 x 500 mm
Installation dimensions (L x W x H) ²⁾	6.850 x 1.490 x 1.730 mm
Machine weight ²⁾	ca. 2.800 kg
Electrical connected load ²⁾	38,50 kW (100 Amp)
Supply voltage (EU)	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz
Marking	CE

Materials

EPS fish boxes pre-shredded, wet

Industries

Fish industry

Fish markets

Delicatessens

Options

Automatic block separating system

Block lifting crane with gripper

Individually customized silo size

Symbol image



¹⁾ Depending on material type and material density ²⁾ Basic machine without silo and options